

1.	Name and unique identification code of the product-type:	Panel PIR SL-BL Polyisocyanurate rigid foam (PIR) panels faced, both sides, with a kraft-aluminium paper complex.
2.	Intended uses of the construction product:	Thermal insulation for buildings (ThIB).
3.	Manufacturer:	Poliuretanos, S.A. Z.I. El Trust, Ctra. C-65, km 16 17244 Cassà de la Selva – Girona (Spain) Tel. +34 972 46 04 72 Fax. +34 972 46 17 19 e-mail: info@poliuretanos.com
4.	System of assessment and verification of constancy of performance of the construction product (AVCP):	AVCP 4 (Reaction to fire) AVCP 3 (Other properties)
5.	Harmonised standard: Notified body/ies: Notified laborator/ies:	EN 13165:2012+A2 :2016 - Centre Scientifique et Technique du Bâtiment (CSTB) , notified testing laboratory N° 0679. APPLUS LGAI Technological Center , notified testing laboratory N° 0370.

DECLARATION OF PERFORMANCE
CPR-2013.29_2
EN 13165:2012+A2 :2016
CSTB N° 0679
APPLUS LGAI N° 0370


6. Declared performance

<i>Essential characteristics</i>	<i>Performance</i>		
Reaction to fire	F		
Water permeability	Water absorption short term	NPD	
	Water absorption long term	WL(T)1	
	Flatness after one-sided wetting	NPD	
Release of dangerous substances to the indoor environment	No harmonised test method available		
Acoustic absorption index	Sound absorption	NPD	
Direct airborne sound insulation index	Sound absorption	NPD	
Continuous glowing combustion	No harmonised test method available		
Thermal resistance	Thermal resistance R_D ($m^2 \cdot K/W$)	$d_N: 40mm R_D=1,85$ $d_N: 80mm R_D=3,70$ $d_N: 48mm R_D=2,20$ $d_N: 90mm R_D=4,15$ $d_N: 52mm R_D=2,40$ $d_N: 95mm R_D=4,40$ $d_N: 56mm R_D=2,60$ $d_N: 100mm R_D=4,65$ $d_N: 61mm R_D=2,80$ $d_N: 105mm R_D=4,85$ $d_N: 68mm R_D=3,15$ $d_N: 112mm R_D=5,20$ $d_N: 75mm R_D=3,45$ $d_N: 120mm R_D=5,55$	
		Thermal conductivity λ_D ($W/m \cdot K$)	0,022
		Thickness $d_N: 40-120$	T2
		Water vapour permeability	Water vapour transmission
Compressive strength	$e \leq 45mm$	CS(10\Y)175	
	$e \geq 50mm$	CS(10\Y)200	
Tensile strength / flexion	Tensile strength perpendicular to faces	NPD	
Durability of reaction to fire against heat, weathering, ageing / degradation	Reaction to fire does not change with time		
Durability of thermal resistance against heat, weathering, ageing/degradation	Thermal resistance and thermal conductivity	(a)	
	Durability of thermal resistance against ageing/degradation	(a)	
	Dimensional stability under specified temperature and humidity conditions	DS(70,90)3	
	Deformation under specified compressive load and temperature conditions	NPD	
	Methods for determination of the values of thermal resistance and thermal conductivity after ageing	(a)	
Durability of compressive strength against ageing/degradation	Compressive creep	NPD	

^(a) The declared value of thermal conductivity incorporates the effect of aging over time extrapolated to 25 years.

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) n° 305/211, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

 **Poliuretanos, s.a.**
 Ctra. C-65, Km. 16.- Pol. Ind el Trust
 Tel. 972 46 04 72 - Fax 972 46 17 19
 F. Bona CASSÀ DE LA SELVA - Girona
 General Manager

Cassà de la Selva, 14.09.2017